

# DRY-ERASE LAMINATION CLEAR PET

**PART#:**  
**LAMDEUV**  
**Dry-Erase Clear**  
**Overlamine**

**CAM DISPLAYS**

## PRINT MEDIA DATA SHEET

Description: 2 mil clear PET lamination. Clear permanent adhesive, and a clear PET release liner. Gloss finish with a "Dry-Erase" coating. Water-based inks write and erase smoothly. Can also be printed with Solvent, Eco-Sol, & UV inks.

- **Smooth writing & dry-erasing**
- **For white boards or walls**
- **Eco-Sol & UV Printable**
- **Up to 2 years outdoor life**

Film	Type/Materials	PET
	Thickness	2mil (50µm) ± 5%
	Transmittance	85%
	Finish	Gloss Smooth writing surface, Dry-erase
Adhesive/Glue	Type/Materials	Solvent-based Acrylic, Clear, Permanent
	Thickness	0.8mil (20µm)
	Initial Tack(N/in <sup>2</sup> ) Glass FTM-9	≥ 8
	Hold Standard: 9.8(N/in <sup>2</sup> ) FTM-3	≥ 48 Hours
	180° Peel Adhesion (N/in <sup>2</sup> ) FTM-1	≥ 11
Liner	Type/Materials	PET Liner
	Thickness	1mil (23µm)
Available Sizes	Widths	54"
	Lengths	98.5' & 164'
Shelf Time		2 Years
Application Temperature Range		From 50° to 150° F
Outdoor Durability		Up to 2 Years

Digital Printer Ink Type	Eco-Solvent	Solvent	UV	Latex/Resin
	Yes	Yes	Yes	

Application	Blockout	Rigid Boards	Simple Curves, Rivets	Vehicle Decals	Floors	Compound Curves	Wall/ Window	Outdoor Signage
		Yes					Yes	Yes

NOTE: All values shown are for reference only. The mentioned data are averages of test results and should not be used for legal or warranty issues.

[www.CamPrint.Media](http://www.CamPrint.Media)