

STANDARD CLEAR VINYL 4mil

PART#:
PMAVC Gloss

CAM DISPLAYS

PRINT MEDIA DATA SHEET

Description: 4 mil calendered monomeric PVC film, coated with clear, solvent-based, permanent acrylic adhesive. Clear thick vinyl, ≤4% opacity. Consistent printing quality from roll-to-roll and batch-to-batch. Thick release liner helps ease application. The Gloss finish is durable and scratch resistant. Perfect for general signage, labels/stickers, boards, and most medium-term indoor and outdoor applications.

- **Consistent print quality**
- **Durable, scratch-resistant**
- **Clear Thick Vinyl**
- **Great value profit-maker**

Film	Type/Materials	Monomeric PVC Gloss
	Caliper/Thickness	4mil (100µm)
	L*a*b* Value	Clear
	Opacity	≤4%
	Finish	≤90 @ 60°
	Elongation at break MD/CD	≥230% / ≥250%
	Shrinkage@72hr MD/CD FTM-14	≤ 0.18mm / ≤ 0.14mm
Adhesive/Glue	Type/Materials	Clear Permanent solvent-based acrylic
	Thickness	1mil (24µm)
	Init Tack @ 20min (N/in ²) FTM-9	≥12
	Hold Standard: 9.8N/in ² FTM-3	≥ 48 Hours
	180° Peeling (N/in ²) FTM-1	≥17 High Tack
Liner	Type/Materials	Single-side PE-Coated White Paper
	Caliper / Weight (oz/yd ²)	4oz (140g/m ²)
Available Sizes	Widths	54" (1.37m) + custom sizes up to 60"
	Lengths	164' (50m)
Shelf Time		≤24 Months
Application Temperature Range		From 50° to 150° F (10° to 65°C)
Outdoor Durability		Up to 1 year

Digital Printer Ink Type	Eco-Solvent	Solvent	UV	Latex/Resin
	Yes	Yes	Yes	*Test

Application	POP/POS Display	Rigid Boards	Windows	Smooth Walls	Labels / Stickers	Vehicle Decals	Outdoor Signage
	Yes	Yes	Yes	Yes	Yes		Yes

NOTE: All values shown are for reference only. The mentioned data are averages of test results and should not be used for legal or warranty issues.

CamDisplays.com