## PREMIUM ADHESIVE VINYL

PART#: PMAVPGR-G Premium Gloss Gray Removable

Description: 3.15 mil polymeric vinyl, coated with gray, solvent based, permanent acrylic adhesive. The polymeric plasticizer is highly conformable over curves with a long outdoor life and minimum shrinkage. The embossed release liner makes micro-channels in the adhesive to enable <u>air-escape</u> when applied, and is a thick 145g paper, PE-coated on both sides to <u>block humidity and prevent</u> <u>curling</u> before and after printing. \*Not for full vehicle wraps or stretching.\* Medium-to-long-term indoor and outdoor use including signage, decals, boards, walls & windows.



## PRINT MEDIA DATA SHEET

- Premium Polymeric Vinyl
- Air-Escape easy apply
- Gray removable adhesive
- High conformability
- Liner PE-coated on both sides

			_							
		Type/Materials				Calendered Polymeric Vinyl Gloss or Matte				
		Caliper/Thickness				3.15mil (80μm) ± 5%				
		L*a*b* Value				96, -1.95, 0.05				
Film		Opacity				≥ 98% with gray adhesive				
		Finish				≥ 80% @ 60°, Matte= 10% @ 60° reflection				
		Elongation at break MD/CD				≥ 230% / 260%				
		Shrinkage MD/CD FTM-14				≤ 0.4mm (1/64") / 0.6mm (1/32") at 72hrs				
		Type/Materials				Solvent-based Acrylic, Gray, Removable				
Adhesive/Glue		Thickness				1.1mil (28µm)				
	e	Initial Tack(N/in²) Glass FTM-9				≥ 5 Medium Tack				
		Hold Standard: 9.8(N/in²) FTM-3				≥ 120 Hours, Removable w/o residue ≤ 2yrs				
	1	180° Peel Adhesion (N/in²) FTM-1				≥ 8				
		Type/Materials				PE-coated Air-Escape Embossed Paper				
Liner	Ca	Caliper(ISO536/534)/Weight (g/m <sup>2</sup> )				6.6mil (170µm) / 145g + 2-sided PE-coating				
					s <mark>39", 54</mark>	39", 54" + Custom sizes up to 63"				
		Lengths				98.5' & 164'				
Shelf Time						2 Years				
Application Temperature Range					From 5	From 50° to 150° F				
Outdoor Durability						3 Years				
			Cal	vant		1 1\ /	Latav	/Decin		
Digital Prin		Eco-Solvent		Solvent		UV		Latex/Resin		
Ink Type	;	Yes		Yes			Yes		Yes	
Application	Block	out Rigid Boards	•	e Curves, ivets	Vehicle Decals	Floors	Compound Curves	Wall/ Window	Outdoor Signage	
	Yes	e for reference only.		/es	Yes	Yes		Yes	Yes	

NOTE: All values shown are for reference only. The mentioned data are averages of test results and should not be used for legal or warranty issues.

## www.CamPrint.Media